MB.1001

BlueLine



MicroBlue

- · Cordless operation
- · Five years warranty

TECHNICAL SPECIFICATIONS

EYEPIECE(S)

- Wide field WF 10x/18 mm eyepiece(s)
- Secured and with pointer for monocular versions

HEAD

- Monocular models with 45° inclined tubes
- Binocular models have 45° inclined tubes, adjustable interpupillary distance between 48 and 75 mm and a \pm 5 diopter adjustment on left tube
- · Trinocular models have 30° inclined tubes, interpupillary distance is adjustable between 48 and 75 mm and equipped with a \pm 5 diopter adjustment on the left tube
- The trinocular head has a fixed light path beamsplitter (50:50) and generates an erect image
- Models with digital head are supplied with a integrated 1.3 MP 1/2.5" CMOS sensor with 1272 x 952 pixel resolution USB 2.0 camera
- LCD version with 5.6" LCD screen
- All heads are 360° rotatable and secured except for the LCD head, which is secured fixed



Monocular head

NOSEPIECE

OBJECTIVES

throughput

immersion are also available



Binocular head

Revolving nosepiece for 3 or 4 reversed objectives on ball bearings

Achromatic 4x/0.10, 10x/0.25 and S40x/0.65. Models with S60X or S100x oil

• The S40x, S60x and S100x oil immersion objectives are spring loaded All optics are anti-fungus treated and anti-reflection coated for maximum light



Trinocular head



to sample and objectives

FOCUSING

Digital monocular head



- Coaxial coarse and fine adjustments, 200 graduations, 15 μm per

· Supplied with an adjustable rack stop to prevent damage

• The coarse adjustments are equipped with friction control

graduation, 3 mm per rotation, total travel approximately 15 mm

Digital LCD head

STAGE

All models are supplied with 115 x 100 mm stage with integrated 55 x 20 mm X-Y mechanical stage, except for the basic model MB.1001 which is supplied with a 105 x 105 mm stage and two non-removable clamps

HIGHLIGHTS Entry-level microscopes · Monocular, binocular and trinocular models

· Digital and LCD models · Revolving reversed nosepiece · Integrated X-Y mechanical stage LED and NeoLED™ illumination · Ergonomic carrying grip



DIGITAL MODELS

CONDENSER

Height adjustable Abbe condenser N.A. 1.25 with iris diaphragm and filter holder, except for the MB.1001 model and MB.1001-LCD models which are equipped with a single N.A. 0.65 condenser with built-in iris diaphragm

ILLUMINATON

- All monocular versions are supplied with an adjustable 1W LED illumination
- The binocular and trinocular versions are supplied with a replaceable 1 W
 NeoLED™ illumination system for increased light output
- All models have internal rechargeable batteries with an external 100-240 V battery charger/mains adapter

PACKAGE CONTENT

- Supplied with mains adapter-charger, white filter, dust cover, user manual and 5 ml immersion oil for models with an S100x objective.
 Software included for digital and LCD models
- All packed in a polystyrene box

CAMERA

- All the MicroBlue build in digital camera microscopes are equipped with a 1.3 MP CMOS USB-2 camera
- Maximum resolution 1272 x 952, 24 bits color depth, up to 30 frames per second
- Delivered with ImageFocus 4 software, USB-2 cable and a micrometer 1mm/100 slide
- · Warranty for the camera is two years

SOFTWARE

- The capture and analysis ImageFocus 4 software allows to save images in .jpg, .tif or .bmp formats as well as .avi format videos
- Images can be annotated and measurements can be performed in live or captured images
- Compatible with Windows 7, 8 and 10, both 32 and 64 bits configurations
- · Mac OS Light version is also available for capturing images
- Updates can be downloaded on our website www.euromex.com

LCD SCREEN

All the MicroBlue LCD microscopes are equipped with 5.6" LCD screen

- Screen resolution 640 x 480
- · Save images and videos directly to SD card
- Image resolution 2048 x 1536, 1600 x 1200, 1280 x 960, 640 x 480
 in JPEG format
- Video resolution 640 x 480 in .AVI format
- Warranty for the camera is 2 years





MODELS	Mono	Bino	Trino	Maximum objectives	4/10/S40x objectives	S60x objective	S100x objective	Mechanical X-Y stage	LED	NeoLED	Batteries
MB.1001				3	•				•		•
MB.1051				4	•			•	•		
MB.1651	•			4	•	•			•		•
MB.1151				4	•		•	•	•		
MB.1052		•		4	•					•	•
MB.1652				4	•	•		•		•	•
MB.1152				4	•		•			•	•
MB.1053				4	•			•		•	•
MB.1653			•	4	•	•				•	
MB.1153				4							

MODELS	Digital LCD	Digital mono	Maximum objectives	4/10/540x objectives	S60x objective	S100x objective	Mechanical X-Y stage	LED	NeoLED	Batteries
MB.1001-LCD*	•		3	•				•		•
MB.1051-LCD*	•		4							
MB.1055			4	•			•		•	•
MB.1655		•	4		•				•	
MB.1155			4			•			•	•

^{*} models with LCD-screen

MB.9981

MB.9991

ACCESSORIES AND SPARE PARTS

MB.6010	Wide field 10x/18 mm eyepiece with pointer	PB.5155	Microscope sli	des 76 x 26 mm, ground edges, 50 pieces			
MB.6010-P	Wide field 10x/18 mm eyepiece with pointer	PB.5157-W	Microscope sli	des 76 x 26 mm, ground edges. White frosted side			
MB.6010-M	Wide field 10x/18 mm eyepiece with micrometer scale		50 pieces per p	pack			
MB.6015	Wide field 15x/11 mm eyepiece	PB.5157-B	Microscope sli	des 76 x 26 mm, ground edges. Blue frosted side,			
MB.6020	Wide field 20x/9 mm eyepiece	x/9 mm eyepiece 50 pieces p					
		PB.5160	Microscope sli	des 76 x 26 mm with cavity, grinded edges. 10			
MB.6099	Pair of eyecups		pieces per pac	k			
		PB.5165	Cover glasses	18 x 18 mm, thickness 0.13-0.17 mm, 100 pieces			
MB.7004	Achromatic 4x/0.10 objective, 35 mm parafocal	PB.5168	Cover glasses 22 x 22 mm, thickness 0.13-0.17 mm, 100 piece				
MB.7010	Achromatic 10x/0.25 objective, 35 mm parafocal	PB.5245	Lens cleaning paper, 100 sheets per pack				
MB.7020	Achromatic 20x/0.40 objective, 35 mm parafocal	PB.5255	Immersion oil,	n = 1.482 (25 ml)			
MB.7040	Achromatic S40x/0.65 objective, 35 mm parafocal	PB.5274	Isopropyl alco	hol 99% (200 ml)			
MB.7060	Achromatic S60x/0.85 objective, 35 mm parafocal	PB.5275	Cleaning kit: le	ens cleaning fluid, lint free lens tissue, brush, air			
MB.7000	Achromatic S100x/1.25 objective, 35 mm parafocal		blower, cotton	swabs			
MB.9710	Frosted filter						
MB.9900	Aluminium transport case	Öã dãã ơ⁄	∘åÆâ^K				
AE.9918	Nylon microscope bag, dimensions 26 x 18 x 400 mm	N	lew York	100 Lauman Lane, Suite A, Hicksville, NY 11 Tel: (877) 877-7274 Fax: (516) 801-2046 Email: Info@nyscopes.com			
MB.9975	External mains/charger adapter 100-240 Vac/5 Vdc (50/60 Hz)		Microscope				
MP 0001	1 W LED ranks coment unit		Company				

Microscope Experts since 1979

1 W LED replacement unit

1W NeoLED replacement unit for binocular MicroBlue

www.microscope international.com

801