



*High Performance USB 3.0 C-mount  
Cooled Monochrome Microscope Camera*

<b>Camera specifications</b>	PC Camera resolution (MP)	20
	Camera resolution (n° of pixels: W x H)	5440x3648
	USB Signal output	USB.3.0
	Color / Monochrome	Monochrome
	Sensor Size	1"
	Sensor Technology	CMOS
	Sensor Type	SONY EXMOR
	Rolling Shutter	Yes
	Image Format	3/2
	Pixel Size (mm)	2.4x2.4
	Frame rate full resolution (fps)	17.8@5440x3648
	Frame rate other resolution (fps)	41 @4096x2160; 51 @2736x1824; 64 @1824x1216
	Dynamic range (DB)	66.30
	G sensitivity	388mV at 1/30s
	Dark Signal	0.21mV at 1/30s
	ADC conversion	14 Bit
	Exposure time	0.1 msec - 3600 sec
	Binning	1x1; 2x2; 3x3
	IR filter	Yes
	IR filter range (nm)	380-650 (IR CUT)
	Cooling	Yes
	Cooling Temperature	-45°C
	Camera Power	PC USB
	Cooling Power	12V 3A
C-Mount	Yes	
Dimensions (mm)	100 (diam) x 100 (H)	
Weight (Kg)	0.59	

<b>Camera accessories</b>	Calibration slide	Yes
	USB cable (1.8m)	Yes

<b>Environment specifications</b>	Working Temperature	-10°C up to +50°C
	Storage Temperature	-20°C up to +60°C
	Relative Humidity	30% to 80%
	Storage Humidity	10% to 60%

<b>Operating System</b>	OS	Windows 7
	OS	Windows 8
	OS	Windows 10 (32Bit)
	OS	Windows 10 (64Bit)
	OS	Osx (MAC Osx) starting from 10.7.5
	OS	Linux
<b>Available Software</b>	SW	PROVIEW
	SW	LITEVIEW
<b>PC requirements</b>	PC	CPU: Intel Core2 - 2.8GZ or higher
	PC	RAM: 2GB or more
	PC	USB 3.0
<b>Warranty</b>	Years	2

Öada~ eAA^K



**New York  
Microscope  
Company**

Microscope Experts since 1979

100 Lauman Lane, Suite A, Hicksville, NY 11801  
 Tel: (877) 877-7274 | Fax: (516) 801-2046  
 Email: [Info@nyscopes.com](mailto:Info@nyscopes.com)  
[www.microscopeinternational.com](http://www.microscopeinternational.com)